



**NOTE:**

1. CABLE: UL2725 28AWG\*1PR+24AWG\*2C+AB, OD: 4.5MM, BLACK COLOR, PVC JACKET  
UL2725 28AWG\*2C +AL, OD: 2.8MM, BLACK COLOR, PVC JACKET
2. CONNECTOR: USB 2.0 AF (WHITE INSULATION, NICKEL PLATED)
3. CONNECTOR: MICRO USB 2.0 BM (BLACK INSULATION, NICKEL PLATED)
4. CONNECTOR: USB 2.0 AM (WHITE INSULATION, NICKEL PLATED)
5. MOLD: 45P PVC BLACK
6. OPEN/SHORT TEST: 100% TEST
7. INSULATION RESISTANCE: 5M OHM MIN.

**WIRE ADDRESS**

| P1      | P2        | P1      | P3      |
|---------|-----------|---------|---------|
| 1 _____ | 1 _____   | 1 _____ | 1 _____ |
| 2 _____ | 2 _____   |         |         |
| 3 _____ | 3 _____   |         |         |
| 4 _____ | 4+5 _____ | 4 _____ | 4 _____ |

|          |  |          |     |      |            |
|----------|--|----------|-----|------|------------|
| ITEM NO. | 19.08.1009   | Draw     | F16 | Date | 2014.10.09 |
| DESC.    | ROLINE USB 2.0 Y Cable<br>AF to AM/Micro BM, 1m, black | Check    |     | Date |            |
|          | Unit(mm)   | Approval |     | Date |            |

**rotronic**

|       |        |      |
|-------|--------|------|
| D     |        |      |
| C     |        |      |
| B     |        |      |
| VER.A | REVISE | Date |