



# Poly Studio G62 Video Conferencing System (99T09AA)

## Übersicht

### Configurable, powerful, all yours



Poly Studio G62 conferencing system features easy setup, seamless integration, and the customization you need. Powerful collaboration tools? Done. Advanced audiovisual options? Check. A flexible setup? You got it[1].

### Designed to connect. Made to expand

Tailor every large conference room to your needs. Connect your Poly peripherals and controllers to the Poly Studio G62 video conferencing system and transform spaces with a modular solution designed for streamlined versatility[1].

### Easy to install. Easier to connect

Forget complex installations. With magnetic mounts and powered by PoE+, you can rest easy knowing installation is a breeze. Plus, you can easily manage select 3rd party control systems with robust APIs while using the Poly TC10 in the room[1].

### Customize your rooms with confidence

Create your ideal large room setup with the Poly Studio G62 video conferencing system. Expand your setup as you see fit without worrying about processing power by adding more A/V devices for a richer, more engaging experience[1].

### A centralized view of the room

Keep an eye on every device. Easily monitor performance, manage, and troubleshoot your Poly Studio G62 video conferencing system and peripherals with the Poly Lens cloud-based device management service even if you're not in the room[1].

# Leistungsmerkmale

## Compact. Customizable. Clutter-free

The Poly Studio G62 video conferencing system makes room integration to select Poly peripherals quick and easy plus more cost-effective via Ethernet so you can customize your setup and deliver a great experience in the room — even at the far end.<sup>[1]</sup>

## The ultimate setup for collaboration

The bigger the space, the more room for distractions. Keep them at bay by pairing the Poly Studio G62 video conferencing system with Poly peripherals that include Poly DirectorAI camera framing and tracking features and NoiseBlockAI.<sup>[1]</sup>

## Integration-ready, right out of the box

Efficiency is the name of the game with the Poly Studio G62 video conferencing system. A compact design and magnetic mounting system make placement a breeze, and you can easily connect it to 3rd party components for a richer overall experience.<sup>[1]</sup>

## No space? No problem

A streamlined setup makes everything easier. With a modular design, IP connectivity, and a single PoE+ powered codec, the Poly Studio G62 video conferencing system adapts perfectly to various room configurations and keeps the space clutter-free.<sup>[1]</sup>

## Device control at your fingertips

Give yourself some peace of mind. Connect and keep an eye on your Poly Studio G62 modular room video conferencing system and Poly peripherals remotely using Poly Lens and save time and effort on device management and maintenance.<sup>[1]</sup>

---

*[1] A complete system includes the Poly Studio G62 paired with Poly camera and audio peripherals. Compatible products include Poly Studio E60 camera, Poly Studio E360 companion camera, Poly Studio E70 camera, Poly Studio R30 USB video bar and Poly IP table and ceiling microphones. Compatible devices need to be network connected for management.*

## Zusätzliche Spezifikationen

<b>Anschlüsse</b>	2 USB Type-A 5Gbps signaling rate; 1 HDMI-in 2.0; 1 line in; 1 line out; 2 HDMI-out 2.0 (video); 1 PoE+ 802.3at-class 4 LAN RJ-45; 1 LLN RJ-45; 1 USB Type-C® 5Gbps signaling rate (with DisplayPort™ Alt Mode for video input)
<b>Audio</b>	Automatic gain control; Automatic noise suppression; Keyboard noise reduction; MMode; NoiseBlockAI; Sound Reflection Reduction; Instant adaptation echo cancellation; Acoustic Fence; Audio error concealment; Siren Lost Packet Recovery technology; Poly Stereo Audio; Active Lip Synchronization
<b>Audiostandards</b>	22 kHz with Polycom Siren 22 technology; 20 kHz with G.719 (M- Mode) and Polycom Siren 22 technology; 14 kHz with Polycom Siren 14 technology, G.722.1 Annex C; 7 kHz with G.722, G.722.1; 3.4 kHz with G.711, G.728, G.729A
<b>Betriebsspannung</b>	50 – 57 V, 30 W (class 4), 45 W (class 5), 60 W (class 6)
<b>Datenblatt Foto 1</b>	AHID/aed257ad4c5f9d4e4cc1442453d56211ff5b7f7c
<b>Datenblatt Foto 2</b>	AHID/98e206d17531144b3959936471d542b5c73011e1
<b>Datenblatt Foto 3</b>	AHID/8ea1d877cbb8d5c4e907c5795e4a2d64f3e40d48
<b>Digitale Beschilderung</b>	Appspace; Raydiant; Zoom
<b>Farbe</b>	Black
<b>Gewicht</b>	1.76 lb
<b>Gewicht</b>	798 g
<b>Harmonized tariff schedule code</b>	85176200000
<b>Herkunftsland</b>	Made in Laos
<b>Herstellergarantie</b>	Poly standard one-year limited warranty
<b>Höhe bei Betrieb</b>	3,048 m
<b>Höhe bei Betrieb</b>	10,000 ft
<b>Interoperabilität</b>	Support for native 3rd party applications including Zoom, Microsoft Teams, Dialpad, GoToRoom, RingCentral and Tencent
<b>Kartons pro Palette</b>	80
<b>Kartons pro Schicht</b>	8
<b>Kompatible Betriebssysteme</b>	Android
<b>Lieferumfang</b>	Ethernet cable; Warranty card; HDMI cable; Poly Studio G62
<b>Luftfeuchtigkeit bei Lagerung</b>	5 to 95%
<b>Luftfeuchtigkeitsbereich im Betrieb</b>	15 to 80%
<b>Mehrere Bestellmengen</b>	5
<b>Mikrofontyp</b>	Up to three IP microphone arrays
<b>Mindestabmessungen (B x T x H)</b>	247.7 x 152.4 x 34.9 mm

<b>Mindestabmessungen (B x T x H)</b>	9.75 x 6 x 1.38 in
<b>Netzteiltyp</b>	External
<b>Netzwerkfunktionen</b>	IPv4; IPv6; Auto-MDIX; H.323 and/or SIP up to 6 Mbps in Poly App video mode; Polycom Lost Packet Recovery (LPR) technology; Reconfigurable MTU size; Web proxy support: basic, digest, and NTLM; 100/1G/2.5G; IP REST & CLI API support; Simple Certificate Enrollment Protocol (SCEP)
<b>Nicht betriebsfähige Temperatur – Celsius</b>	-40 to 70 °C
<b>Nicht betriebsfähige Temperatur – Fahrenheit</b>	-40 to 158 °F
<b>Paketabmessungen (B x T x H)</b>	304.8 x 187.3 x 84.1 mm
<b>Paketabmessungen (B x T x H)</b>	12 x 7.38 x 3.31 in
<b>Paketgewicht</b>	3.07 lb
<b>Paketgewicht</b>	1390 g
<b>Palette (Schichten)</b>	10
<b>Palettenabmessungen</b>	47.24 x 39.37 x 87.16 in
<b>Palettenabmessungen (B x T x H)</b>	120 x 100 x 221.4 cm
<b>Palettgewicht</b>	787.05 lb
<b>Palettgewicht</b>	357 kg
<b>Produkte pro Palette</b>	400
<b>Produkte pro Palettenschicht</b>	40
<b>RMA-Nummer</b>	PBJ-STG-62R; PBJ-STG-62N
<b>Sicherheitsmanagement</b>	802.1x support
<b>Spezielle Merkmale</b>	Speaker framing; People framing; Group framing; Presenter tracking; DirectorAI perimeter supported <sup>[4]</sup>
<b>Stromversorgung</b>	Power over Ethernet (PoE+), compatible with IEEE 802.3at/bt class 4, 5, 6 switch, or PoE injector <sup>[1,2]</sup>
<b>Technische Daten zur Nachhaltigkeit</b>	80% post-consumer recycled plastic; Packaging is recyclable; At least 20% recycled metal
<b>Temperaturbereich bei Betrieb</b>	0 to 40°C
<b>Temperaturbereich bei Betrieb</b>	32 to 104 °F
<b>UNSPSC-Code</b>	45111902
<b>UPC-Nummer</b>	197961146721
<b>Verwaltungssoftware</b>	Poly Lens
<b>Videoauflösung von Inhalten (Ausgang)</b>	UHD (3840 x 2160); HD (1920 x 1080); HD (1280 x 720)
<b>Videoauflösung von Inhalten (Eingang)</b>	UHD (3840 x 2160); HD (1920 x 1080); WSXGA+ (1680 x 1050); SXGA (1280 x 1024); HD (1280 x 720); XGA (1024 x 768); SXGA+ (1400 x 1050)

<b>Videoauflösung von Personen</b>	4K, 30 fps (TX and RX) from 2048 Kbps; 1080p, 60 fps from 1740 Kbps; 1080p, 30 fps from 1024 Kbps; 720p, 60 fps from 832 Kbps; 720p, 30 fps from 512 Kbps; 4K, 30 fps from 3200 Kbps
<b>Videobildfrequenz</b>	30 fps (up to 4K resolution)
<b>Videostandards</b>	H.264 AVC; H.264 High Profile; H.265; H.264 SVC; H.263; RTV; H.263 video error concealment; H.264 video error concealment; H.239 Polycom People+Content
<b>Wireless-Technologien</b>	802.11 a/b/g/n/ac/ax Wireless; Bluetooth® 5.1; Multiple-Input Multiple-Output (MIMO) <sup>[3]</sup>
<b>Zertifizierte Kollaborationssoftware</b>	Microsoft Teams; Poly Video
<b>Zertifizierungen und Compliance</b>	CB; FCC; IC; RCM; VCCI; UL/CSA; CE; WEEE; UKCA; MIC

[1] Sold separately.

[2] PoE+ switch must be configured to 30 W or more.

[3] Not available on no radio versions.

[4] Poly peripherals may be needed to enable these features.

## Haftungsausschluss — Copyright

© Copyright 2024 HP Development Company, L.P. Änderungen vorbehalten. Neben der gesetzlichen Gewährleistung gilt für HP Produkte und Dienstleistungen ausschließlich die Herstellergarantie, die in den Garantieerklärungen für die jeweiligen Produkte und Dienstleistungen explizit genannt wird. Aus den Informationen in diesem Dokument ergeben sich keinerlei zusätzliche Gewährleistungsansprüche. HP haftet nicht für technische bzw. redaktionelle Fehler oder fehlende Informationen.